

Specifications (Subject to change without notice.)



Welding Mode	Input Power	Welding Amperage Range	Rated Output	Amps Input at Rated Load Output, 50/60 Hz,						Max. Open-Circuit Voltage	Dimensions	Net Weight
				115 V	230 V	400 V	460 V	KVA	KW			
TIG (GTAW)	3-phase	1–200 A	175 A at 17 V, 60% duty cycle	—	10.5	6.0	5.2	4.2	4.0	80 VDC (9–14 VDC**)	H: 13.5 in. (343 mm) W: 7.5 in. (191 mm) D: 17.5 in. (445 mm) with Contractor Kit 69 lb. (31.3 kg)	
	1-phase	1–200 A 1–150 A (120 V)	175 A at 17 V, 60% duty cycle	—	17.4	—	—	4.0	4.0			
			150 A at 16 V, 70% duty cycle	29.7	14.1	—	—	3.4	3.4			
			125 A at 15 V, 100% duty cycle	23.0	—	—	—	2.6	2.6			
Stick (SMAW)	3-phase	1–200 A	150 A at 26 V, 60% duty cycle	—	13.1	7.4	6.4	5.2	5.0	80 VDC (9–14 VDC**)	H: 46.25 in. (1175 mm) W: 23.5 in. (597 mm) D: 22.25 in. (565 mm) with TIGRunner® 129 lb. (58.5 kg)	
	1-phase	1–200 A	150 A at 26 V, 60% duty cycle	—	21.7	—	—	5.0	5.0			
				—	0.23*	—	—	0.05*	0.02*			
		1–90 A	125 A at 25 V, 50% duty cycle	34.1	—	—	—	4.0	3.8			
			90 A at 24 V, 100% duty cycle	25.0	—	—	—	4.0	3.8			